



## High Shrinkage PVC Stock Film #2183

### **SECTION 1 - IDENTIFICATION**

**Product Name:** PVC Shrink Film

**Material Thickness:** 45 Micron

**Product Grade:** Stock 2183

**2183 Description:** High-shrinkage grade displaying ultimate shrinkage values over 60%. Easy to use with excellent printability. Great choice for a range of full-body labeling applications.

**Chemical Name:** Polyvinyl Chloride (PVC) Film

**Product Use:** Packaging, labeling, etc. – This product is considered an article under OSHA Hazard Communication Standard (29 CFR 1910.1200 (b)(6)(v)).

### **SECTION 2 – HAZARDS IDENTIFICATION**

**Hazards Identification:** Repacorp PVC Shrink Film is expected to be a low hazard for usual industrial or commercial handling and is not considered a hazardous chemical per OSHA's Hazard Communication Standard.

### **SECTION – 3**

**Components:**

- Polyvinyl Chloride

### **SECTION – 4**

**Disposal Considerations:**

Recycle or reuse product when applicable. Dispose of in accordance with federal, state and local regulations through recycling, incineration or landfill.



## High Shrinkage PVC Stock Film #2183

### SECTION 5 – Additional Technical Information

- Store in a cool, dry area. Avoid excessive heat or cold. Avoid excessive humidity or dryness.
- Avoid storage near ignition sources.
- PVC film contains hydrogen chloride, carbon dioxide and other toxic gases when burned. Exposure to combustion products may be fatal over prolonged periods and should be avoided.

